



## MA 283 D/S SL

### GENERAL TECHNICAL CHARACTERISTICS

Structure: enamelled steel, closed firebox  
 Firebox: In Aluker®  
 Fire pit: in cast iron  
 Hood: in steel  
 Opening: door in enamelled steel with self-cleaning ceramic glass resistant up to 750 C°  
 Rise n fall door, hinged opening for cleaning  
 Door profile: in enamelled steel  
 Door handle: in enamelled steel  
 Primary air: adjustable manually  
 Secondary air: fixed  
 Flue outlet top  
 Flue damper: manual  
 Ash pan: removable  
 Fuel: wood  
 Heating: radiant and natural convection

### TECHNICAL DATA

Room heating capacity (m <sup>2</sup> in-max)	m <sup>2</sup>	200 - 345
Nominal thermal efficiency	%	> 70
Rated heat output	KW	12
Consumption at rated heat output	Kg/h	4,5
Maximum heat output	KW	13
Maximum consumption	Kg/h	5,3
Flue outlet	Ø cm	25
Flue up to 4,5 mt	Ø cm	30
Flue over 4,5 mt	Ø cm	25
Fresh air intake (recomm. m <sup>2</sup> in sect.)	cm <sup>2</sup>	300
Weight	Kg	185

### ON REQUEST

- Cooking Pro kit
- Adjustable legs kit
- Positioning handles kit

Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used



The availability of models may vary from Country to Country.

Compatible Cover



### TECHNICAL DRAWING

